

APPLICATIONS



Water pressure boosting in individual houses / bungalows / apartments / farm houses

FEATURES

- Adjustable cutin and cutout pressure
- Silent running
- Rust-proof material
- Built-in thermal protection
- Automatic on / off
- Flow upto 6000 lph
- Head upto 60 m
- Power upto 2 hp
- Compact design
- Designed for high start / stop per hour

ACCESSORIES

- Pump
- Tank
- Pressure switch
- Pressure gauge
- Cable with plugs



DIMENSIONS

MODEL	100	230	250	110	120	130
DIMENSION (lxdxh)	47.5x27.5x51.6	47.5x29x55	47.5x29x55	37x23x38.5	39.2x23x38.5	42x23x38.5
TANK SIZE (Lts)	20	24	24	20	24	24
SUCTION / DELIVERY SIZE (mm)	25	25	25	25	25	25

HYDRAULIC PERFORMANCE

MODEL	MOTOR (HP)	FLOW (m ³ /hr)	0.6	1.2	1.8	2.4	3	3.6	4.2	4.8	5.4
Ecomatic 100	0.5	Head(m)	37.5	32.5	25	14	0				
Ecomatic 110	0.5		37.5	32.5	27.5	20	12	0			
Ecomatic 120	0.75		45	40	34	25	15	0			
Ecomatic 130	0.75		47	44	38	34	27	20	10	0	
Ecomatic 230	0.75		33	32	30	27	24	20	16	12	7
Ecomatic 250	1		56	54	50	45	40	35	27	20	11

Single phase - 220 - 240 v X 50Hz

Sold and serviced in India by:

GRUNDFOS PUMPS INDIA PRIVATE LTD.

118 Old Mahabalipuram Road, Thoraiakkam, Chennai 600 097
Toll free: 1800 - 345 - 4555. Email: salesindia@grundfos.com

- Chennai: 0 9840944720 • Mumbai: 0 9987264514 • New Delhi: 0 9910005316
- Bangalore: 0 9945684103 • Hyderabad: 0 9963007733 • Kolkata: 0 9830345072
- Pune: 020 - 32403640 • Ahmedabad: 079 - 40063618 • Maldives: 0 9607793720
- Kochi: 0 9895758124 • Surat: 0 9725045271 • Chandigarh: 097791 25824
- Indore: 0 9893098763 • Jaipur: 0 9829036168 • Madurai: 0 9940112407
- Nagpur: 0 9970182577 • Coimbatore: 0 9791011130 • Raipur: 0 99935 83536
- Bhubaneswar: 0 99370 34044



Product picture may differ from actual product. Specifications and performance data are subject to change without prior notice.