

DRAINER PUMPS FOR WASTE WATER



The Drainer pump is designed for liquid transfer and drainage of clean or slightly dirty wastewater with the pump completely or partly submerged in the liquid.

The pump can be used for automatic as well as manual operation and can be installed permanently or used as a portable pump.

The AP pump is a single-stage submersible pump designed for the pumping of drainage and effluent

Applications

- Drainage of cellars or buildings
- Pumping of waste water in buildings.
- Groundwater lowering.
- Drainage in places prone to flooding.
- Empty applications, e.g. Pools, tanks and vessels
- Dewatering of construction sites and excavations
- Pumping of domestic wastewater without discharge from water closets

Salient Features

- Enclosure Class - IP 58
- Insulation Class: "F"
- Fully automatic
- Complete SS Pump
- Max. particle handling size upto 50 mm
- Max. Temperature upto 55° C

Available range

Model	Power range (kW) (P2)	Max. Flow (LPH)	Max. head (mts)	Max. liquid temp.	Max. Particle handling size (mm)
KP	0.3 - 0.7	12000	9	50°C	10
AP 12	0.4 - 1.1	30000	16	55°C	12
AP 35	0.6 - 0.8	20000	11	55°C	35
AP 50	0.8 - 1.1	32000	11	55°C	50