

SOLOLIFT CC

APPLICATIONS

Sololift + lifting stations are a practical and attractive solution for discharging domestic effluent from basement toilets to the sewage pipe directly.

- The Sololift+ units grind and evacuate sewage and wastewater quickly - upto 1 litre per second - and automatically to a maximum height of 5 meters and upto 100 meters from the main sewage pipe.
- They are the ideal solution for rapid instalment of an additional convenience and avoid costly or unattractive connections.
- Wide range (refer to the table on the bottom of the page)



SALIENT FEATURES

Compact tanks fitted with a pump and:

- A stainless steel cutting blade and a strainer basket for grinding and centrifuging of organic matter and toilet tissue, (Sololift + WC version)
- A level switch for automatic start / stop
- A Ø 32 connector for discharge piping with Ø23,25 and 28 reducers depending on the model, a Ø40 rubber sleeve inlet, and 2 fasteners for fixing to the ground.
- The WC models are prefitted with a DN100 pan connector with a sealing sleeve suitable for floor-mounted or wall mounted pans.
- Maximum liquid temperature : 40°C 70°C Sololift C-3 (2min)
- 1.2 metres cable with plug.
- Spout with active carbon filter
- IP 44 motor - Insulation Class F
- Voltage : 1x230V, 50Hz

TECHNICAL FEATURES

PUMPS	Diameter (mm)		Power (W)	Dimensions									
	Discharge	Inlet (Connections)		H	L	W	l/min	30	40	45	50	55	60
Sololift+ WC	23/25/28/32	100	400	280	431	190	mts (head)	6.8	6.2	5.8	5.6	5.0	4.8
Sololift+ WC-1	23/25/28/32	100+3x40	400	280	431	190		6.8	6.2	5.8	5.6	5.0	4.8
Sololift+ WC-3	23/25/28/32	100+3x40	400	280	431	190		6.8	6.2	5.8	5.6	5.0	4.8
Sololift+ CWC-3	23/25/28/32	100+3x40	350	298	476	138		4.8	4.2	3.8	3.4	3.0	2.4
Sololift+ C-3	23/25/28/32	3x40	300	298	476	138		4.4	3.8	3.4	2.8	2.4	1.8
Sololift+ D-3	23/32	1x40+1x40/32	270	144	296	162		4.2	3.6	2.8	2.0	1.4	-