

# UNILIFT CC

## APPLICATIONS

Unilift CC are multi-purpose submersible drainage pumps designed to handle clean water, groundwater and grey wastewater with particles size up to 10 mm.

The pump must be completely or partly submerged in the liquid.

## FEATURES

- Low-suction ability-down to 3 mm when the strainer is removed
- Suitable for continuous operation
- Adaptor for easy connection and non-return valve included
- Easy float switch adjustment to control start/stop levels
- Ceramic shaft seal with triple seals for efficient motor protection
- Includes built-in thermal overload protection
- Integrated Ventilation Valve



## CONSTRUCTION

- The Motor is cooled by the pumped liquid passing between the stainless steel part of the motor and motor sleeve
- Composite and stainless steel materials
- Robust stainless steel strainer which allows free passage for particles size up to 10 mm
- Ceramic seal
- IP68 motor, class B Insulation

## Available Range

Model	Power (P1) (watts)	Flow (m <sup>3</sup> /hr)	Head (mts)									Discharge pipe size	Max. particle size (mm)	Weight (kgs)	
			1	2	3	4	5	6	7	8	9				
CC5	240		4.8	3	2	1							1 1/4	10	4.35
CC7	380		9	8	6.5	5	3.2	1.8	0.5				1 1/4	10	4.6
CC9	780		14	13.2	12	10.5	9	7.5	6	4	1.5		1 1/4	10	6.5

Voltage : 1 X 220 - 240 Volts / 50Hz

BE > THINK > INNOVATE >